

This page describes the predefined [Wiki Styles](#) and how a [Wiki Administrator](#) can define additional [Wiki Styles](#) as a local customization for all pages (in local/config.php) or specific groups (in local/\$Group.php).

All predefined [Wiki Styles](#) are setup in the global array [\\$WikiStyle](#).

To define your own [Wiki Styles](#), add the setting of the correspondent WikiStyle within the array.

Predefined Wiki Styles

The following array-values are set by scripts/wikistyles.php using the [SDV\(\)-function](#) (so you can overwrite them by setting them prior in config.php or farmconfig.php):

markup:	definition:
text colors: (equiv. to %define=xxxx color=xxxx%)	
%black%	\$WikiStyle['black']['color'] = 'black';
%white%	\$WikiStyle['white']['color'] = 'white';
%red%	\$WikiStyle['red']['color'] = 'red';
%yellow%	
%blue%	\$WikiStyle['blue']['color'] = 'blue';
%gray%	\$WikiStyle['gray']['color'] = 'gray';
%silver%	

```
$WikiStyle['yellow']['color'] =  
'yellow';
```

```
$WikiStyle['silver']['color'] =  
'silver';
```

%maroon%	\$WikiStyle['maroon']['color'] = 'maroon';
%green%	\$WikiStyle['green']['color'] = 'green';
%navy%	\$WikiStyle['navy']['color'] = 'navy';
%purple%	

```
$WikiStyle['purple']['color'] =
'purple';
```

list-styles:	
%decimal%	\$WikiStyle['decimal']['apply'] = 'list';
%roman%	\$WikiStyle['roman']['apply'] = 'list';
%ROMAN%	\$WikiStyle['ROMAN']['apply'] = 'list-decimal-roman';
%alpha%	\$WikiStyle['ROMAN']['apply'] = 'list-upper-roman';

```
$WikiStyle['alpha']['list-style']  
= 'lower-alpha';
```

%ALPHA%	\$WikiStyle['ALPHA']['apply'] = 'list';
special:	\$WikiStyle['ALPHA']['list-style']
open links in a new browser-window	upper-alpha';
%newwin%	
Turns markup into a comment via display:none CSS	
%comment%	

Author-Defined Wiki Styles

1. The first index of the array defines the style name (e.g. mynewstyle, projectentry etc)
2. the second index defines the attribute name (e.g. color, background-color, etc.)
3. the value set defines the attribute value (e.g. red, bold, #00ffcc, etc.)

Sample: If you want to define a (site-wide) style the same as the page style

```
%define=projectentry color:red%
```

use

```
$WikiStyle['projectentry']['color'] = 'red';
```

The \$WikiStyle['projectentry']['apply'] variable may be defined if the wikistyle concerns a particular tag. It may be 'item' (for li|dt), 'list' (for ul|ol|dl), 'div', 'pre', 'img', 'p' or the combining 'block' (for p|div|ul|ol|dl|li|dt|pre|h[1-6]). Example:

```
$WikiStyle['top']['apply'] = 'item'; $WikiStyle['top']['class'] = 'top';
$WikiStyle['newwin']['target'] =
'_blank';
```

then a markup

```
* %top% An important list-item
```

```
will output $WikiStyle['comment']['display']
= 'none';
```

```
<li class="top">An important list-item</li>
```

Printer-Friendly Styles

If your custom-styles (in local/config.php) are getting very colorful it might be useful to disable them in print-view. This can be done easily by putting them into a condition.

```
if($action!="print") { // your custom-styles }
```

Notes

To be done:

Questions:

I tried this but background didn't work, thou border and float worked? /Vincent 2008-04-08

```
$WikiStyle['vMenu']['background']='#ffffcc' ;  
$WikiStyle['vMenu']['float']='left' ; $WikiStyle['vMenu']['border']='1px dotted  
red' ;
```

Try using `$WikiStyle['vMenu']['background-color']='#ffffcc'` ; -- unlike background, background-color is defined in the `$WikiStyleCSS` array, which is checked for valid properties.

Q: How would i set an image to the left of a paragraph in a [Wiki Style??](#) I'd like to provide an icon for paragraphs that are notes, important, warnings, etc.

See [WikiStylesPlus](#) and [Callout](#).