

[Pm Wiki](#) has the capability to stage *draft* versions of a page prior to them becoming "official". All of the draft pages end in "-Draft" by default (this can be changed by setting [\\$DraftSuffix](#)). Multiple interim edits to a page can be temporarily saved in a "-Draft" copy of a page until the draft is ready to be published to the original.

When the site administrator sets [\\$EnableDrafts](#) in a local customization file, the "Save" button on the edit page is split into separate "Publish" and "Save draft" buttons.

The "Save draft" button causes any edits to be saved to a "-Draft" copy of the original page, leaving the original page intact. Subsequent requests to edit the page (either the original or -Draft) bring up the draft copy for further editing.

The "Publish" button saves back to the original non-Draft copy of the page, removing any -Draft page that may have been created.

By default, saving drafts and publishing are available to anyone with 'edit' permissions (see [Passwords](#)). However, the site administrator can also set the [\\$EnablePublishAttr](#) configuration variable, which provides a separate 'publish' permission that is required to publish to the original page.

Drafts and pagelists (and RSS)

The drafts module also sets pagelists (and thus RSS feeds) to ignore "-Draft" pages by default; one has to do `list=all` or similar in order to have draft pages included in a pagelist or RSS feed.

How do I moderate all postings?

Start by [enabling drafts](#) to change the "Save" button into separate "Publish" and "Save draft" buttons. Then set [\\$EnablePublishAttr](#). This adds a "publish" authorization level to distinguish editing of page drafts from publishing.