

This page describes some of the internal workings of [Pm Wiki](#) by explaining how some of the functions in pmwiki.php work. For a more brief list/overview on functions useful to for instance cookbook writers, see [Cookbook:Functions](#).

To use this functions you have to make sure that all relevant internal variables have been initialized correctly. See [Custom Markup](#) and [Custom Actions](#) for more information on how these functions are typically called via Markup() or \$HandleActions[].

## PSS(\$string)

The PSS() function removes the backslashes that are automatically inserted in front of quotation marks by the /e option of PHP's preg\_replace function. PSS() is most commonly used in replacement arguments to Markup(), when the pattern specifies /e and one or more of the parenthesized subpatterns could contain a quote or backslash. ("PSS" stands for "Pm Wiki Strip Slashes".)

From PM: Pm Wiki expects PSS() to always occur inside of double-quoted strings and to contain single quoted strings internally. The reason for this is that we don't want the \$1 or \$2 to accidentally contain characters that would then be interpreted inside of the double-quoted string when the PSS is evaluated.

```
Markup('foo', 'inline', '/(something)/e', 'Foo(PSS("$1"))'); # wrong
Markup('foo', 'inline', '/(something)/e', "Foo(PSS('$1'))"); # right
```

## Example

This is a fictitious example where PSS() should be used. Let us assume that you wish to define a directive (:example:) such that (:example "A horse":) results in the HTML

```
<div>"A horse"</div>.
```

Here is how the markup rule can be created:

```
Markup('example', 'directives', '/\\(:example\\s(. *?):\\)/e',
"Keep('<div>'.PSS('$1').'</div>')");
```

We need to use PSS() around the '\$1' because the matched text could contain quotation marks, and the /e will add backslashes in front of them.

## stripmagic(\$string)

This function should be used when processing the contents of \$\_POST or \_GET variables when they could contain quotes or backslashes. It verifies get\_magic\_quotes(), if true, strips the automatically inserted escapes from the string.

## **FmtPageName(\$fmt, \$pagename)**

Returns `$fmt`, with `$variable` and `$(internationalisation)` substitutions performed, under the assumption that the current page is `pagename`. See [PmWiki.Variables](#) for an (incomplete) list of available variables, [PmWiki.Internationalizations](#) for internationalisation. Security: not to be run on user-supplied data.

This is one of the major functions in Pm Wiki, see [PmWiki.FmtPageName](#) for lots of details.

## **Markup(\$name, \$when, \$pattern, \$replace)**

Adds a new markup to the conversion table. Described in greater detail at [PmWiki.CustomMarkup](#).

This function is used to insert translation rules into the Pm Wiki's translation engine. The arguments to `Markup()` are all strings, where:

`$name` The string names the rule that is inserted. If a rule of the same name already exists, then this rule is ignored. `$when` This string is used to control *when* a rule is to be applied relative to other rules. A specification of "`<xyz`" says to apply this rule prior to the rule named "xyz", while "`>xyz`" says to apply this rule after the rule "xyz". See [CustomMarkup](#) for more details on the order of rules. `$pattern` This string is a [regular expression](#) that is used by the translation engine to look for occurrences of this rule in the markup source. `$replace` This string will replace the matched text when a match occurs.

Also see: [PmWiki.CustomMarkup](#) and [Cookbook:Functions#Markup](#)

## **MarkupToHTML(\$pagename, \$str)**

Converts the string `$str` containing Pm Wiki markup into the corresponding HTML code, assuming the current page is `$pagename`.

Also see: [Cookbook:Functions#MarkupToHTML](#)

## **mkdirp(\$dir)**

The function `mkdirp($dir)` creates a directory, `$dir`, if it doesn't already exist, including any parent directories that might be needed. For each directory created, it checks that the permissions on the directory are sufficient to allow Pm Wiki scripts to read and write files in that directory. This includes checking for restrictions imposed by PHP's `safe_mode` setting. If `mkdirp()` is unable to successfully create a read/write directory, `mkdirp()` aborts with an error message telling the administrator the steps to take to either create `$dir` manually or give Pm Wiki sufficient permissions to be able to do it.

## MakeLink(\$pagename, \$target, \$txt, \$suffix, \$fmt)

The function `MakeLink($pagename, $target, $txt, $suffix, $fmt)` returns a `???`. Its arguments are as follows:

`$pagename` is the source page `$target` is where the link should go `$txt` is the value to use for '`$Link Text?`' in the output `$suffix` is any suffix string to be added to `$txt` `$fmt` is a format string to use

If `$txt` is NULL or not specified, then it is automatically computed from `$target`.

If `$fmt` is NULL or not specified, then [Make Link?](#) uses the default format as specified by the type of link. For page links this means the `$LinkPageExistsFmt` and `$Link Page Create Fmt?` variables, for intermap-style links it comes from either the `$IMapLinkFmt` array or from `$UrlLinkFmt`. Inside of the formatting strings, `$LinkUrl` is replaced by the resolved url for the link, `$Link Text?` is replaced with the appropriate text, and `$LinkAlt` is replaced by any "title" (alternate text) information associated with the link.

Also see: [PmWiki:MakeLink](#) and [Cookbook:Functions#MakeLink](#)

## MakeUploadName(\$pagename, \$x)

[Make Upload Name?](#) ( ) simply takes a string `$x` (representing an attachment's name) and converts it to a valid name by removing any unwanted characters. It also requires the name to begin and end with an alphanumeric character, and as of 2.0.beta28 it forces any file extensions to lowercase. This function is defined in `scripts/upload.php` and only used when uploads are enabled.

## SessionAuth(\$pagename, \$auth=NULL)

[Session Auth?](#) ( ) manages keeping authentication via cookie-sessions. `Session` contains ever password or validated id and associated groups from previous calls. It adds elements passed by `$auth` to session. It also writes every element saved in session to `$AuthPw@@(passwords)` and `@@$Auth List?(ids and groups)`.

## IsAuthorized(\$chal, \$source, &\$from)

[Is Authorized?](#) takes a `pageattributesstring` (e. g. "id:user1 \$1\$Ff3w 34 HASH?...") in `$chal`. `$source` is simply returned and used for building the `authcascade` (`pageattributes - groupattributes - $DefaultPassword@@`). `@@$from` will be returned if `$chal` is empty, because it is not checked before calling [Is Authorized?](#) ( ), this is needed for the `authcascade`. [Is Authorized?](#) ( ) returns an

array  
with three values: \$auth@@ @@1@@ - authenticated, @@0@@ - not authenticated, @@-1@@ - refused; @@\$passwd;  
\$source from the parameter list.

## CondAuth (\$pagename, 'auth level')

CondAuth implements the [ConditionalMarkup](#) for (:if auth level:). For instance CondAuth(\$pagename, 'edit') is true if authorization level is 'edit'. Use inside local configuration files to build conditionals with a check of authorization level, similar to using (:if auth level:) on a wiki page.

Note that [Cond Auth?\(\)](#) should be called after all authorization levels and passwords have been defined. For example, if you use it with [Drafts](#), you should include the draft.php script before calling [Cond Auth?\(\)](#):

```
$EnableDrafts = 1; $DefaultPasswords['publish'] = crypt('secret');  
include_once("$FarmD/scripts/draft.php"); if (! CondAuth($pagename, 'edit')) {  
/* whatever */ }
```

Best is to use [Cond Auth?\(\)](#) near the bottom of your config.php script.

## [Retrieve Auth Page?\(\\$pagename, \\$level, \\$authprompt=true, \\$since=0\)](#)

Pm words as said in

<http://article.gmane.org/gmane.comp.web.wiki.pmwiki.user/12493/match=retrieveauthpage%%>

where:

\$pagename - name of page to be read \$level - authorization level required (read/edit/auth/upload) \$authprompt - true if user should be prompted for a password if needed \$since - how much of the page history to read 0 == read entire page including all of history READPAGE\_CURRENT == read page without loading history timestamp == read history only back through timestamp

The \$since parameter allows Pm Wiki to stop reading from a page file as soon as it has whatever information is needed -- i.e., if an operation such as browsing isn't going to need the page's history, then specifying READPAGE\_CURRENT can result in a much faster loading time. (This can be especially important for things such as searching and page listings.)

Use e.g. \$page = @RetrieveAuthPage('Main.MyPage', 'read') to obtain a page object that contains all the information of the correspondent file in separate keys, e.g. \$page['text'] will contain a string with the current wiki markup of [Main.My Page?](#). Use this generally in preference to the alternative function ReadPage(\$pagename, \$since=0) since it respects the authorisation of the user, i.e. it checks the authorisation level before loading the page, or it can be set to do so. ReadPage() reads a page regardless of permission.

Passing 'ALWAYS' as the authorization level (instead of 'read', 'edit', etc.) will cause [Retrieve Auth Page?](#) to always read and return the page, even if it happens to be protected by a read password.

**[Retrieve Auth Section?](#)(\$pagename, \$pagesection, \$list=NULL, \$auth='read')**

[Retrieve Auth Section?](#) extracts a section of text from a page. If \$pagesection starts with anything other than '#', it identifies the page to extract text from. Otherwise RetrieveAuthSection looks in the pages given by \$list, or in \$pagename if \$list is not specified.

- The selected page is placed in the global \$RASPageName variable.
- The caller is responsible for calling Qualify() as needed.

Provides a way to limit the array that is returned by [Read Page?](#), so that it only pulls the content up to a specific section marker. For example, pulling from start of page to '##blogend':

```
function FeedText($pagename, &$page, $tag) { $text =  
RetrieveAuthSection($pagename, '##blogend'); $content = MarkupToHTML($pagename,  
$text); return "<$tag><![CDATA[$content]]></$tag>"; }
```

The '##blogend' argument says to read from the beginning of the page to just before the line containing the marker. See

[IncludeOtherPages](#) for more information about the section specifications.

This version won't read text from pages that are read-protected; if you want to get text even from read-protected pages, then

```
$text = RetrieveAuthSection($pagename, '##blogend', NULL, 'ALWAYS');
```

**[Update Page?](#)(\$pagename, \$old (page object), \$new (page object));**

### [More Technical Notes](#)

UpdatePage() allows cookbook recipes to mimic the behavior of editing wiki pages via the browser. Internally, Pm Wiki does several house keeping tasks which are accessible via this function (preserving history/diff information, updating page revision numbers, updating [Recent Changes?](#) pages, sending email notifications, etc.)

- "Page object" refers to an array pulled from ReadPage(\$pagename); Note that \$new['text'] should contain all page data for the new version of the page.
- If a page doesn't exist, [Update Page?](#)() will attempt to create it.
- Ignoring \$old (e.g. UpdatePage(\$pagename, '', \$new);) will erase all historical page data---a *tabula rasa*.

[Update\\_Page?](#) ( ) cannot be called directly from config.php because there are necessary initializations which occur later in pmwiki.php. It is not enough to just load stdconfig.php. If you want to use [Update\\_Page?](#) ( ) you will need to do it within a [custom markup](#), a [custom markup expression](#), or a [custom action](#).