

`$EnableLinkPageRelative` When enabled, causes [Pm Wiki](#) to use relative urls for page links instead of absolute urls.

```
$EnableLinkPageRelative = 1;
```

[\\$PagePathFmt](#) This array lists the order in which Pm Wiki looks for the page that you *most likely* are attempting to link to. The default is listed below. Look at [Cookbook:PagePaths](#) for some ideas.

```
array( '{ $Group}.$1', '$1.$1' . '$1.{ $DefaultName}' )
```

[\\$LinkPageExistsFmt](#) The (HTML) string to output for links to already existing wiki pages. Defaults to

[\ \\$LinkText](#)

[\\$LinkPageCreateFmt](#) The (HTML) string to output for links to non-existent wiki pages. The default is to add a '?' after the link text with a link to the page edit/create form. Defaults to

[\ \\$LinkText ?](#)

`: $LinkPageCreateSpaceFmt`: Same as [\\$Link Page Create Fmt?](#), but used when the link text has a space in it.

[\\$LinkPageSelfFmt](#) The (HTML) string to output for self-referencing links (i.e. links to the page itself). Defaults to

[\ \\$LinkText](#)

[\\$UrlLinkFmt](#) The (HTML) string to output for URL-links that begin with 'http:', 'ftp:', etc. Defaults to

[\ \\$LinkText](#)

`$IMapLinkFmt` an array of link formats for various link "schemes". Not set as default.

Examples of custom formats to allow different styling via classes:

Links to http: standard url links:

```
$IMapLinkFmt['http:'] = "\ \$Link Text?";
```

Links to https: secure pages:

```
$IMapLinkFmt['https:'] = "\ \$Link Text?";
```

Links to Pm Wiki: [Inter Map](#) shortcut:

```
$IMapLinkFmt['PmWiki:'] = "\ \$Link Text?";
```

`$InterMapFiles` An array consisting a list of files and pages containing [Inter Map](#) entries to be loaded (see [CustomInterMap](#)).

[\\$MakePageNameFunction](#) Name of a custom function to replace `MakePageName()`, which converts strings into valid page names.

`$MakePageNamePatterns`: [\\$ Make Page Name Patterns ?](#) is an array of regular expression replacements that is used to map the page link in a *free link* such as `[[ free link ]]` into a page name. Currently the default sequence is

```
"/'/" => '', # strip single-quotes "/[^$PageNameChars]+/" => ' ', # convert
non-alnums to spaces "/((^[^-\w])\w)/e" => "strtoupper('$1')", # initial caps
after spaces "/" /" => ' ' # strip spaces
```

Note that if you change \$MakePageNamePatterns, the documentation links may break. This can be fixed by re-setting \$

[Make Page Name Patterns ?](#) to the default in local/Pm Wiki.php.

[\\$WikiWordCountMax](#) The maximum number of times to convert each [Wiki Word](#) encountered on a page. Defaults to 1,000,000. Common settings for this variable are zero (disable [Wiki Word](#) links) and one (convert only the first occurrence of each [Wiki Word](#)).

```
\$WikiWordCountMax = 0; # disable Wiki Word links \$WikiWordCountMax = 1; # convert only first Wiki Word
```

:[\\$WikiWordCount](#):An array that allows the number of WikiWord conversions to be set on a per-WikiWord basis. The default is to use [\\$Wiki Word Count Max?](#) unless a value is set in this array. By default Pm Wiki sets [\\$WikiWordCount](#)['Pm Wiki']=1 to limit the number of conversions of "Pm Wiki".

```
\$WikiWordCount['PhD']=0; # Don't convert "PhD" \$WikiWordCount['Wiki Word']=5; # Convert Wiki Word
5 times # the following lines keep a page from linking to itself $title = FmtPageName('$Title_', $pagename);
\$WikiWordCount[$title]=0;
```

[\\$EnableRedirectQuiet](#)Enable the quiet=1 parameter for the [redirect directive](#). On publicly edited wikis it is advisable not to enable quiet redirects.

```
\$EnableRedirectQuiet = 0; # disable quiet redirects (default)
\$EnableRedirectQuiet = 1; # enable quiet redirects
```